



Where everyday's a *Sun* day ...™

SOLAR HOT WATER

APPLICATIONS

- Domestic Hot Water
- Radiant Floor Space Heating
- Swimming Pools
- Food Processing
- Car Washes
- Restaurants
- Laundromats
- Farms



SAVE OVER 80%
OF YOUR HOT WATER NEEDS

TAX/UTILITY
INCENTIVES AVAILABLE



THE EarthNet ENERGY[®] ADVANTAGE

ENE 24 EVACUATED TUBE COLLECTOR

- INCREASED MANIFOLD PIPE DIAMETER ALLOWING:
 - HIGHER FLOW RATES
 - GREATER HEAT TRANSFER
 - HIGHER OPERATING TEMPERATURES
 - HIGHER BTU PRODUCTION
- HIGH PERFORMANCE INSULATION REDUCE HEAT LOSS AND IMPROVE HEAT TRANSFER
- CERTIFIED "L" COPPER MANIFOLD TESTED TO 725 PSI
- COMPONENTS ARE POWDER COATED STEEL FOR LONGEVITY

HIGH EFFICIENT SOLAR TANK

- HYDRASTONE LINING FOR HIGH EFFICIENCY HEAT RETENTION AND PREVENTION FROM CORROSION
- DENSE URETHANE FOAM INSULATION TO R-16
- RUST/MAINTENANCE-FREE PLASTIC JACKET
- 20 SQ. FT. COPPER-FINNE SOLAR REMOVABLE HEAT EXCHANGER

SOLAR DISSIPATION KIT

- DISSIPATES UP TO 15,000 BTUs/HOUR
- INCLUDES 24 VOLT 3-WAY VALVE AND TRANSFORMER
- PREVENTS SYSTEM FROM OVERHEATING



ADVANCED SOLAR CONTROL MODULE

- VARIABLE SPEED PUMP
- SD CARD FOR MONITORING & GRAPHING SYSTEM RESULTS
- INCLUDES FILL, FLUSH, DRAIN AND BALANCING VALVES
- THERMOMETER AND PRESSURE GEAR WITH SAFETY VALVE

RACKING SYSTEMS

- RACKING SYSTEMS DESIGNED FOR ADJUSTABILITY AND EASE OF INSTALLATION
- HEAVY DUTY STEEL RACKING
- POWDER COATED RACKING PARTS AND ACCESSORIES FOR GREATER DURABILITY, LONGEVITY, AND APPEARANCE
- ENGINEERED TO ADAPT TO A VARIETY OF INSTALLATIONS
- PITCHED, FLAT ROOF AND GROUND MOUNTING KITS FOR ANY APPLICATION
- CUSTOMIZED LEG LENGTHS FOR ADJUSTABILITY

A u t h o r i z e d D e a l e r

Collector Specifications		Absorber Specifications	
Collector Number of Tubes	24	Vacuum Tube	Borosilicate glass
Collector Dimensions (LxWxH)	114.25"x86.0"x7.75"	Wall Thickness (Tube)	0.098 inches (2.5mm)
Collector Surface Area	67.45 s.f.	Tube Outside Diameter	4.0 inches (100mm)
Collector Absorber Surface Area	45 s.f. (4.2m ²)	Tube Length	78.74 inches (2000mm)
Collector Angle of Inclination	15° 90°	Tube Weight	10.14 pounds (4.6 kg)
Collector Weight	383 pounds	Tube Vacuum	99.99999 (>10 ⁻³ Pa)
Collector Test Pressure	260 psi	Hailstone Resistant to	1.378 in (35mm) dia
Collector Operating Pressure	100psi	Light Transmission of Glass	91%
Collector Fluid Content	.6274 gal (2.375 L)	Absorber Material	Copper/Aluminum
Collector Operating Temperature	Up to 240°F	Absorber Coating	Aluminium Nitride (Al-N-O)
Module Max Temperature	374°F (190°C)	Absorption Coefficient	>92%
Heating Capacity	51,000 BTUs/Day	Emmission Coefficient	<8%
Heat Dissipator	15,000 BTUs/Hour	Stagnation Temperature	477°F (247°C)
Certificates & Global Approvals	SPF, DIN4757, TUV, EN12975, SRCC	Angle of Operating Inclination	15° to 90°

95 BRIM BLVD CHAMBERSBURG, PA 17201
717-414-7652 WWW.EARTHNETENERGY.NET